

90-1 Polyolefin Protective Tape

Description:

Designed for the protection of acrylic/polycarbonate lens during fabrication and assembly. Unique co-polymer adhesive provides clean and easy removal. Excellent choice for decorative interior trims as well. Available in transparent blue and clear or printed "remove at dealer" in yellow. Provided perforated in roll form. Ask about our outline perforations manufactured to your exact requirements.

Typical Properties:

Material:	Polyolefin
Film Type/Thickness:	.00275"
Adhesive:	Acrylic
Adhesion Level	
Polycarbonate*:	0.875 oz/in
Steel*:	6.5 oz/in
Elongation:	350% Min.
Tensile Strength:	6 lbs/in.

*ADHESION VALUE DETERMINED AS ADHESIVE ONLY

Rev. 1

WALCO MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The Typical Properties listed above are not to be construed as specification. User is responsible for determining whether the Walco product is fit for a particular purpose and is suitable for a user's method of application. Walco assumes no obligations or liability for any advice furnished by it, or for results obtained with respect to any product(s). All such advice is given at the buyer's risk, regardless of the legal theory asserted.

Limitation of Remedies and Liability: If the Walco product is proved to be defective, THE EXCLUSIVE REMEDY, AT WALCO'S OPTION, SHALL BE TO REFUND NO MORE THAN THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE WALCO PRODUCT PROVEN TO BE DEFECTIVE. In no event shall Walco be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability. No waiver, alteration, additions or modifications of the foregoing conditions shall be valid unless made in writing and manually signed by an officer of Walco Corporation.