



# Sales Product Information Sheet

**90-3530**

## **Automotive Protective Tape**

### **Description:**

Best protection solution for freshly painted car bodies. Applied after the painting process, this provides protection for painted surfaces susceptible to damage. Due to the good UV-resistance and perfect paint compatibility, Walco's 90-3530 is the most reliable way to protect cars during the transportation process.

### **Typical Properties:**

Backing Material:	Polyolefin Film
Total Thickness:	3.1 mil.
Adhesive Type:	Synthetic Elastomer
Adhesion to Steel*:	8.2 oz./inch
Elongation at Break:	800%
Color:	White
UV-Resistance:	52 Weeks

\*ADHESION VALUE DETERMINED AS ADHESIVE ONLY

Rev. 1

WALCO MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The Typical Properties listed above are not to be construed as specification. User is responsible for determining whether the Walco product is fit for a particular purpose and is suitable for a user's method of application. Walco assumes no obligations or liability for any advice furnished by it, or for results obtained with respect to any product(s). All such advice is given at the buyer's risk, regardless of the legal theory asserted.

Limitation of Remedies and Liability: If the Walco product is proved to be defective, THE EXCLUSIVE REMEDY, AT WALCO'S OPTION, SHALL BE TO REFUND NO MORE THAN THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE WALCO PRODUCT PROVEN TO BE DEFECTIVE. In no event shall Walco be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability. No waiver, alteration, additions or modifications of the foregoing conditions shall be valid unless made in writing and manually signed by an officer of Walco Corporation.